

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
17 June 2004 (17.06.2004)

PCT

(10) International Publication Number
WO 2004/049946 A1

(51) International Patent Classification⁷: **A61B 6/00**

(21) International Application Number:
PCT/FI2003/000930

(22) International Filing Date: 4 December 2003 (04.12.2003)

(25) Filing Language: Finnish

(26) Publication Language: English

(30) Priority Data:
20022148 4 December 2002 (04.12.2002) FI

(71) Applicant (for all designated States except US): **PLAN-
MED OY** [FI/FI]; Asentajankatu 6, FIN-00880 Helsinki
(FI).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **STRÖMMER,**

Pekka [FI/FI]; Päivänkaari 6 D, FIN-02210 Espoo (FI).
SULIN-SAARISTO, Timo [FI/FI]; Keijukaistenpolku
4 A 23, FIN-00820 Helsinki (FI). **VIRTA, Arto** [FI/FI];
Marjanientie 9 A, FIN-00930 Helsinki (FI).


(74) Agent: **TAWAST, Juha**; Planmed Oy, Asentajankatu 6,
FIN-00880 Helsinki (FI).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR,
CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD,
GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN,
MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU,
SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,

[Continued on next page]

(54) Title: DIGITAL IMAGING METHOD AND APPARATUS FOR MAMMOGRAPHY



(57) Abstract: The invention generally relates to imaging of an object by electromagnetic radiation, especially to digital mammography performed by scanning technique. According to the invention, movement of a digital sensor of a mammography apparatus, synchronized with scanning movement of the beam, is performed by keeping the active surface of the sensor essentially at right angles to the beam, on a plane formed by scanning movement of the beam, while at the same time distance from the sensor to the radiation source is continuously adjusted so that its path in the direction of scanning movement of the beam becomes essentially linear.

WO 2004/049946 A1



ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,
SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*